

KernowPrint FloorShark Dry Toner P46

P46 is a textured white R10 slip resistant Dry Toner print receptive PET film, with an optimised pressure sensitive adhesive for floor graphic applications.

Property	Typical Value	Unit	Test Method
Construction			
Total Thickness	11.8 +/- 0.24	mil	ISO 534
Total Weight	346 +/- 8	gsm	ISO 536
Face Material (with PSA)			
Thickness	7.1 +/- 0.2	mil	ISO 534
Weight	216 +/- 6	gsm	ISO 536
Adhesive			
Thickness	1.06 +/- 0.2	mil	ISO 534
180° Peel Adhesion (SS)	8.5 +/- 1.5	N/25mm	FINAT 1 (Modified) 25mm strip/ 30min dwell
Adhesive Application Temperature	+41 to +122	°F	Internal Method
Adhesive Service Temperature	-40 to +356	°F	Internal Method
Liner			
Liner Thickness	4.7 +/- 0.12	mil	ISO 534
Liner Weight	130 +/- 3	gsm	ISO 536

Attributes

- Unique sharkskin coating, Toner bonding & scratch resistant
- No lamination required
- R10 slip certified (DIN 51130:2014). Low Slip Potential in dry & wet conditions (BS7976-2:2002+A1:2013)
- Durable surface, resists scuffing & stiletto heels
- Also perfect for application to short-pile carpet tiles
- Easy to apply & easy to remove

Recommended Conditions

Print room	50°F - 86°F	30% - 65% RH
Usage	-40°F - 356°F	10% - 90% RH
Storage	50°F - 68°F	20% - 50% RH

www.kernowna.com
 info@kernowna.com
 T: (855) 537-6691

Registered in England
 No. 1092182
 A Member of the Sensitisers
 Group of Companies